



Applications

Features

- Small dimensions
- 6 turns
- Friction clutch on mechanical end-stops (continuous)
- 15 Mio. turns
- Very good resolution, better 0,1%

Options

- Shaft diameter 6.35 mm
(max. length 25 mm)
- Shaft diameter 3 mm
(max. length 10 mm)
- Customer specific cable length
- Tandem-ganged potentiometer
- Wiper protection resistance
- Connection by wires

Standards		
Insulating resistance (500 VDC, 1bar, 2s)	1	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (Amax = 0.75mm, f = 30 ... 2000 Hz)	10	g
Shock (half sine pulse, 7 ms)	30	g

Subject to change
without notice
State: 15-Nov-2005



- Fork-lifter

- ## Features
- Small dimensions
 - 10 turns
 - Friction clutch on mechanical end-stops (continuous)
 - 15 Mio. turns
 - Excellent linearity
 - Very good resolution, better 0,1%

- Shaft diameter 6.35 mm (max. length 25 mm)
- Shaft diameter 3 mm (max. length 10 mm)
- Customer specific cable length
- Tandem-ganged potentiometer
- Wiper protection resistance
- Connection by wires

Standards		
Insulating resistance (500 VDC, 1bar, 2s)	1	GOhm
Dielectric strenght (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (Amax = 0.75mm, f = 30 ... 2000 Hz)	10	g
Shock (half sine pulse, 7 ms)	30	g

Subject to change
without notice
State: 15-Nov-2005



- Fork-lifter

- Fork-lifter

- Small dimensions
- 25 turns
- Friction clutch on mechanical end-stops (continuous)
- 15 Mio. turns
- Excellent linearity
- Very good resolution, better 0,1%

- Shaft diameter 6.35 mm
(max. length 25 mm)
- Shaft diameter 3 mm
(max. length 10 mm)
- Customer specific cable length
- Tandem-ganged potentiometer
- Wiper protection resistance
- Connection by wires

Subject to change
without notice
State: 15-Nov-2005



- Fork-lifter

- ### Features
- Small dimensions
 - 50 turns
 - Friction clutch on mechanical end-stops (continuous)
 - 15 Mio. turns
 - Excellent linearity
 - Very good resolution, better 0.1%

Options

- Shaft diameter 6.35 mm (max. length 25 mm)
- Shaft diameter 3 mm (max. length 10 mm)
- Customer specific cable length
- Tandem-ganged potentiometer
- Wiper protection resistance
- Connection by wires

Standards		
Insulating resistance (500 VDC, 1bar, 2s)	1	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (Amax = 0.75mm, f = 30 ... 2000 Hz)	10	g
Shock (half sine pulse, 7 ms)	30	g

Subject to change
without notice
State: 15-Nov-2005



ML100

Applications

- Fork-lifter

Features

- Small dimensions
- 100 turns
- Friction clutch on mechanical end-stops (continuous)
- 15 Mio. turns
- Excellent linearity
- Very good resolution, better 0,1%

Options

- Shaft diameter 6.35 mm (max. length 25 mm)
- Shaft diameter 3 mm (max. length 10 mm)
- Customer specific cable length
- Tandem-ganged potentiometer
- Wiper protection resistance
- Connection by wires

Subject to change
without notice
State: 15-Nov-2005

CONTELEC

Electrical Data		
Nominal resistance	1/5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±0.25	% of meas. range
Electrical angle	34560	°
Repeatability	3.46	°
Temperature coefficient of the voltage divider	50	ppm/° C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	5	mA
Power rating P	0.25	W/40° C
Min. life (electrical)	15 Mio.	turns
Mechanical Data		
Mechanical range	100	turns
Adjusting speed	max. 1800	° /s
Min. life (mechanical)	15 Mio.	turns
Operating temperature	-25 ... +75	° C
Storage temperature	-25 ... +105	° C
Protection class	IP65	
Standards		
Insulating resistance (500 VDC, 1bar, 2s)	1	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (Amax = 0.75mm, f = 30 ... 2000 Hz)	10	g
Shock (half sine pulse, 7 ms)	30	g